


# Recursion

CSC212: Data Structures



# Recursion

- ❖ Sometimes, certain statements in an algorithm are repeated on different sizes of an input instance.
- ❖ Repetition can be achieved in two different ways.
  - **Iteration:** uses **for** and **while** loops
  - **Recursion:** function calls itself

## Example -1:

- Factorial Function
- Factorial function of any integer  $n$  is defined as

$$n! = \begin{cases} 1 & \text{if } n = 0 & \leftarrow \text{Base Case} \\ n(n-1)! & \text{if } n \geq 1 & \leftarrow \text{Recursion Case} \end{cases}$$

- This is recursive definition. It consists of two parts:
  - Base case**
  - Recursive case**

# Recursion

## Example -1 (Continue) :

- It can be written as:

$$\text{fact}(n) = \begin{cases} 1 & \text{if } n = 0 & \leftarrow \text{Base Case} \\ n \cdot \text{fact}(n-1) & \text{if } n \geq 1 & \leftarrow \text{Recursion Case} \end{cases}$$

where  $\text{fact}(n)$  is the function that calculates  $n!$ .

# Recursion

## Example -1 (Continue) :

– Implementation

### Recursive:

```
public static int recursiveFact(int n)
{
    if(n==0) return 1;
    else
        return n*recursiveFact(n-1);
}
```

### Iterative:

```
public static int iterativeFact(int n)
{
    int fact = 1;
    for(i = 1; i <= n; i++)
        fact=fact*i;
    return fact;
}
```

# Recursive Trace

- ❖ A graphical representation of recursive calls.
- ❖ It is used to analyze the algorithm.

## Example -2:

- Recursive trace for `recursiveFact(4)`

```
public static int recursiveFact(int n)
{
    if(n==0)
        return 1;
    else
        return n*recursiveFact(n-1);
}
```

# Recursive Trace

- ❖ A graphical representation of recursive calls.
- ❖ It is used to analyze the algorithm.

## Example -2:

- Recursive trace for `recursiveFact(4)`

`recursiveFact(4)`

$4 * ? = ?$

```
public static int recursiveFact(int n)
{
    if (n==0)
        return 1;
    else
        return n*recursiveFact(n-1);
}
```

# Recursive Trace

- ❖ A graphical representation of recursive calls.
- ❖ It is used to analyze the algorithm.

## Example -2:

– Recursive trace for `recursiveFact(4)`

recursiveFact(4)

4\*?=?



recursiveFact(3)

3\*?=?

```
public static int recursiveFact(int n)
{
    if (n==0)
        return 1;
    else
        return n*recursiveFact(n-1);
}
```

# Recursive Trace

- ❖ A graphical representation of recursive calls.
- ❖ It is used to analyze the algorithm.

## Example -2:

– Recursive trace for `recursiveFact(4)`

recursiveFact(4)

4\*?=?

recursiveFact(3)

3\*?=?

recursiveFact(2)

2\*?=?

```
public static int recursiveFact(int n)
{
    if (n==0)
        return 1;
    else
        return n*recursiveFact(n-1);
}
```



# Recursive Trace

- ❖ A graphical representation of recursive calls.
- ❖ It is used to analyze the algorithm.

## Example -2:

– Recursive trace for `recursiveFact(4)`

recursiveFact(4)

4\*?=?

recursiveFact(3)

3\*?=?

recursiveFact(2)

2\*?=?

recursiveFact(1)

1\*?=?

```
public static int recursiveFact(int n)
{
    if (n==0)
        return 1;
    else
        return n*recursiveFact(n-1);
}
```

# Recursive Trace

- ❖ A graphical representation of recursive calls.
- ❖ It is used to analyze the algorithm.

## Example -2:

– Recursive trace for `recursiveFact(4)`

recursiveFact(4)

4\*?=?

recursiveFact(3)

3\*?=?

recursiveFact(2)

2\*?=?

recursiveFact(1)

1\*?=?

recursiveFact(0)

```
public static int recursiveFact(int n)
{
    if (n==0)
        return 1;
    else
        return n*recursiveFact(n-1);
}
```

# Recursive Trace

- ❖ A graphical representation of recursive calls.
- ❖ It is used to analyze the algorithm.

## Example -2:

– Recursive trace for `recursiveFact(4)`

recursiveFact(4)

4\*?=?

recursiveFact(3)

3\*?=?

recursiveFact(2)

2\*?=?

recursiveFact(1)

1\*1=1

recursiveFact(0)

1

```
public static int recursiveFact(int n)
{
    if (n==0)
        return 1;
    else
        return n*recursiveFact(n-1);
}
```

# Recursive Trace

- ❖ A graphical representation of recursive calls.
- ❖ It is used to analyze the algorithm.

## Example -2:

– Recursive trace for `recursiveFact(4)`

recursiveFact(4)

4\*?=?

recursiveFact(3)

3\*?=?

recursiveFact(2)

2\*?=?

recursiveFact(1)

1\*1=1


```
public static int recursiveFact(int n)
{
    if (n==0)
        return 1;
    else
        return n*recursiveFact(n-1);
}
```

# Recursive Trace

- ❖ A graphical representation of recursive calls.
- ❖ It is used to analyze the algorithm.

## Example -2:

– Recursive trace for `recursiveFact(4)`



# Recursive Trace

- ❖ A graphical representation of recursive calls.
- ❖ It is used to analyze the algorithm.

## Example -2:

– Recursive trace for `recursiveFact(4)`

recursiveFact(4)

4\*?=?

recursiveFact(3)

3\*?=?

recursiveFact(2)

2\*1=2


```
public static int recursiveFact(int n)
{
    if (n==0)
        return 1;
    else
        return n*recursiveFact(n-1);
}
```

# Recursive Trace

- ❖ A graphical representation of recursive calls.
- ❖ It is used to analyze the algorithm.

## Example -2:

– Recursive trace for `recursiveFact(4)`



# Recursive Trace

- ❖ A graphical representation of recursive calls.
- ❖ It is used to analyze the algorithm.

## Example -2:

– Recursive trace for `recursiveFact(4)`

recursiveFact(4)

$4 * ? = ?$



recursiveFact(3)

$3 * 2 = 6$

```
public static int recursiveFact(int n)
{
    if (n==0)
        return 1;
    else
        return n*recursiveFact(n-1);
}
```




# Recursive Trace

- ❖ A graphical representation of recursive calls.
- ❖ It is used to analyze the algorithm.

## Example -2:

– Recursive trace for `recursiveFact(4)`




```
public static int recursiveFact(int n)
{
    if (n==0)
        return 1;
    else
        return n*recursiveFact(n-1);
}
```

# Recursive Trace

- ❖ A graphical representation of recursive calls.
- ❖ It is used to analyze the algorithm.

## Example -2:

- Recursive trace for `recursiveFact(4)`



```
public static int recursiveFact(int n)
{
    if (n==0)
        return 1;
    else
        return n*recursiveFact(n-1);
}
```

# Main Types of Recursion

❖ Linear Recursion

❖ Binary Recursion

# Linear Recursion

In this case a recursive method makes at most one recursive call each time it is invoked.

## Example – 3:

- **Problem:** Given an array  $A$  of  $n$  integers, find the sum of first  $n$  integers.
- **Observation:** Sum can be defined recursively as follows:

$$\text{Sum}(n) = \begin{cases} A[0] & \text{if } n = 0 & \leftarrow \text{Base Case} \\ \text{Sum}(n-1) + A[n-1] & \text{if } n \geq 1 & \leftarrow \text{Recursive Case} \end{cases}$$

# Linear Recursion

## Example – 3 (Continued):

### – Algorithm

**Sum(A, n)**

**Input:** An integer array **A** and an integer  $n \geq 1$ , such that **A** has at least  $n$  elements

**Output:** The sum of the first  $n$  integers in **A**.

**Processing:**

if  $n = 1$ ;

return  $A[0]$ ;

→ base case

else

return  $\text{Sum}(A, n-1) + A[n-1]$ ; → recursive case.

### Note:

- Base case should be defined so that every possible chain of recursive calls eventually reach a base case.
- Algorithm must start by testing a set of base cases.
- After testing for base cases perform a single recursive call.

# Linear Recursion

## Example – 3 (Continued):

- Recursive trace for  $\text{sum}(A, n)$ , where  $A = \{4, 3, 6, 2, 5\}$ ,  $n=5$

A	
0	4
1	3
2	6
3	2
4	5

### Sum(A, n)

**Input:** An integer array  $A$  and an integer  $n \geq 1$ , such that  $A$  has at least  $n$  elements

**Output:** The sum of the first  $n$  integers in  $A$ .

**Processing:**

if  $n = 1$ ;

    return  $A[0]$ ;                       $\rightarrow$  base case

else

    return  $\text{Sum}(A, n-1) + A[n-1]$ ;                       $\rightarrow$  recursive case.

# Linear Recursion

## Example – 3 (Continued):

- Recursive trace for  $\text{sum}(A, n)$ , where  $A = \{4, 3, 6, 2, 5\}$ ,  $n=5$

**Sum(A,5)**

??+A[4]=??+5=?

A	
0	4
1	3
2	6
3	2
4	5

### Sum(A, n)

**Input:** An integer array  $A$  and an integer  $n \geq 1$ , such that  $A$  has at least  $n$  elements

**Output:** The sum of the first  $n$  integers in  $A$ .

**Processing:**

if  $n = 1$ ;

return  $A[0]$ ;

→ base case

else


return  $\text{Sum}(A, n-1) + A[n-1]$ ;

→ recursive case.

# Linear Recursion

## Example – 3 (Continued):

- Recursive trace for  $\text{sum}(A, n)$ , where  $A = \{4, 3, 6, 2, 5\}$ ,  $n=5$



### Sum(A, n)

**Input:** An integer array  $A$  and an integer  $n \geq 1$ , such that  $A$  has at least  $n$  elements

**Output:** The sum of the first  $n$  integers in  $A$ .

**Processing:**

if  $n = 1$ ;

return  $A[0]$ ;

→ base case

else

return  $\text{Sum}(A, n-1) + A[n-1]$ ;


→ recursive case.



# Linear Recursion

## Example – 3 (Continued):

- Recursive trace for  $\text{sum}(A, n)$ , where  $A = \{4, 3, 6, 2, 5\}$ ,  $n=5$



### **Sum(A, n)**

**Input:** An integer array  $A$  and an integer  $n \geq 1$ , such that  $A$  has at least  $n$  elements

**Output:** The sum of the first  $n$  integers in  $A$ .

**Processing:**

if  $n = 1$ ;

return  $A[0]$ ;

→ base case

else


return  $\text{Sum}(A, n-1) + A[n-1]$ ;

→ recursive case.

# Linear Recursion

## Example – 3 (Continued):

- Recursive trace for  $\text{sum}(A, n)$ , where  $A = \{4, 3, 6, 2, 5\}$ ,  $n=5$



### Sum(A, n)

**Input:** An integer array  $A$  and an integer  $n \geq 1$ , such that  $A$  has at least  $n$  elements

**Output:** The sum of the first  $n$  integers in  $A$ .

**Processing:**

if  $n = 1$ ;

    return  $A[0]$ ;

→ base case

else


    return  $\text{Sum}(A, n-1) + A[n-1]$ ;

→ recursive case.

# Linear Recursion

## Example – 3 (Continued):

- Recursive trace for  $\text{sum}(A, n)$ , where  $A = \{4, 3, 6, 2, 5\}$ ,  $n=5$



### Sum(A, n)

**Input:** An integer array  $A$  and an integer  $n \geq 1$ , such that  $A$  has at least  $n$  elements

**Output:** The sum of the first  $n$  integers in  $A$ .

**Processing:**

if  $n = 1$ ;

return  $A[0]$ ;

→ base case

else


return  $\text{Sum}(A, n-1) + A[n-1]$ ;

→ recursive case.

# Linear Recursion

## Example – 3 (Continued):

- Recursive trace for  $\text{sum}(A, n)$ , where  $A = \{4, 3, 6, 2, 5\}$ ,  $n=5$



### Sum(A, n)

**Input:** An integer array  $A$  and an integer  $n \geq 1$ , such that  $A$  has at least  $n$  elements

**Output:** The sum of the first  $n$  integers in  $A$ .

**Processing:**

if  $n = 1$ ;

return  $A[0]$ ;

→ base case

else


return  $\text{Sum}(A, n-1) + A[n-1]$ ;

→ recursive case.

# Linear Recursion

## Example – 3 (Continued):

- Recursive trace for  $\text{sum}(A, n)$ , where  $A = \{4, 3, 6, 2, 5\}$ ,  $n=5$



### Sum(A, n)

**Input:** An integer array  $A$  and an integer  $n \geq 1$ , such that  $A$  has at least  $n$  elements

**Output:** The sum of the first  $n$  integers in  $A$ .

**Processing:**

if  $n = 1$ ;

return  $A[0]$ ;

→ base case

else


return  $\text{Sum}(A, n-1) + A[n-1]$ ;

→ recursive case.

# Linear Recursion

## Example – 3 (Continued):

- Recursive trace for  $\text{sum}(A, n)$ , where  $A = \{4, 3, 6, 2, 5\}$ ,  $n=5$



### **Sum(A, n)**

**Input:** An integer array  $A$  and an integer  $n \geq 1$ , such that  $A$  has at least  $n$  elements

**Output:** The sum of the first  $n$  integers in  $A$ .

**Processing:**

if  $n = 1$ ;

return  $A[0]$ ;

→ base case

else


return  $\text{Sum}(A, n-1) + A[n-1]$ ;

→ recursive case.

# Linear Recursion

## Example – 3 (Continued):

- Recursive trace for  $\text{sum}(A, n)$ , where  $A = \{4, 3, 6, 2, 5\}$ ,  $n=5$



### **Sum(A, n)**

**Input:** An integer array  $A$  and an integer  $n \geq 1$ , such that  $A$  has at least  $n$  elements

**Output:** The sum of the first  $n$  integers in  $A$ .

**Processing:**

if  $n = 1$ ;

return  $A[0]$ ;

→ base case

else


return  $\text{Sum}(A, n-1) + A[n-1]$ ;

→ recursive case.

# Linear Recursion

## Example – 3 (Continued):

- Recursive trace for  $\text{sum}(A, n)$ , where  $A = \{4, 3, 6, 2, 5\}$ ,  $n=5$



### Sum(A, n)

**Input:** An integer array  $A$  and an integer  $n \geq 1$ , such that  $A$  has at least  $n$  elements

**Output:** The sum of the first  $n$  integers in  $A$ .

**Processing:**

if  $n = 1$ ;

return  $A[0]$ ;

→ base case

else

return  $\text{Sum}(A, n-1) + A[n-1]$ ;


→ recursive case.



# Linear Recursion

## Example – 3 (Continued):

- Recursive trace for  $\text{sum}(A, n)$ , where  $A = \{4, 3, 6, 2, 5\}$ ,  $n=5$



### Sum(A, n)

**Input:** An integer array  $A$  and an integer  $n \geq 1$ , such that  $A$  has at least  $n$  elements

**Output:** The sum of the first  $n$  integers in  $A$ .

**Processing:**

if  $n = 1$ ;

return  $A[0]$ ;

→ base case

else


return  $\text{Sum}(A, n-1) + A[n-1]$ ;

→ recursive case.

# Linear Recursion

## Example – 3 (Continued):

- Recursive trace for  $\text{sum}(A, n)$ , where  $A = \{4, 3, 6, 2, 5\}$ ,  $n=5$



### Sum(A, n)

**Input:** An integer array  $A$  and an integer  $n \geq 1$ , such that  $A$  has at least  $n$  elements

**Output:** The sum of the first  $n$  integers in  $A$ .

**Processing:**

if  $n = 1$ ;

return  $A[0]$ ;

→ base case

else


return  $\text{Sum}(A, n-1) + A[n-1]$ ;

→ recursive case.

# Linear Recursion

## Example – 3 (Continued):

- Recursive trace for  $\text{sum}(A, n)$ , where  $A = \{4, 3, 6, 2, 5\}$ ,  $n=5$



### Sum(A, n)

**Input:** An integer array  $A$  and an integer  $n \geq 1$ , such that  $A$  has at least  $n$  elements

**Output:** The sum of the first  $n$  integers in  $A$ .

**Processing:**

if  $n = 1$ ;

    return  $A[0]$ ;                      → base case


else

    return  $\text{Sum}(A, n-1) + A[n-1]$ ;                      → recursive case.

# Linear Recursion

## Example – 3 (Continued):

- Recursive trace for  $\text{sum}(A, n)$ , where  $A = \{4, 3, 6, 2, 5\}$ ,  $n=5$



### Note:

- For an array of size  $n$ ,  $\text{Sum}(A, n)$  makes  $n$  calls.
- Each spends a constant amount of time.
- So time complexity is  $O(n)$ .

# Binary Recursion

In this case, a recursive algorithm makes two recursive calls.

## Example – 4

- **Problem:** Find the sum of  $n$  elements of an integer array  $A$ .
- **Algorithm:**
  - Recursively find the sum of elements in the **first half** of  $A$ .
  - Recursively find the sum of elements in the **second half** of  $A$ .
  - Add these two values

A	
0	6
1	5
2	3
3	2
4	8

### BinarySum( $A, i, n$ )

**Input:** An integer array  $A$  and an integer  $n \geq 1$ , such that  $A$  has at least  $n$  elements

**Output:** The sum of the first  $n$  integers in  $A$ .

**Processing:**

if  $n = 1$

return  $A[i]$ ;

Else

return BinarySum( $A, i, \lceil n/2 \rceil$ ) + BinarySum( $A, i + \lceil n/2 \rceil, \lfloor n/2 \rfloor$ );

# Binary Recursion

## Example – 4 (Continued):

- Recursive trace


BinarySum (A,0,5)

A	
0	6
1	5
2	3
3	2
4	8

# Binary Recursion

## Example – 4 (Continued):

- Recursive trace




# Binary Recursion

## Example – 4 (Continued):

- Recursive trace

	A
0	6
1	5
2	3
3	2
4	8






# Binary Recursion

## Example – 4 (Continued):

- Recursive trace

	A
0	6
1	5
2	3
3	2
4	8




# Binary Recursion

## Example – 4 (Continued):

- Recursive trace

	A
0	6
1	5
2	3
3	2
4	8




# Binary Recursion

## Example – 4 (Continued):

- Recursive trace

	A
0	6
1	5
2	3
3	2
4	8




# Binary Recursion

## Example – 4 (Continued):

- Recursive trace

	A
0	6
1	5
2	3
3	2
4	8




# Binary Recursion

## Example – 4 (Continued):

- Recursive trace

	A
0	6
1	5
2	3
3	2
4	8




# Binary Recursion

## Example – 4 (Continued):

- Recursive trace

	A
0	6
1	5
2	3
3	2
4	8




# Binary Recursion

## Example – 4 (Continued):

- Recursive trace

	A
0	6
1	5
2	3
3	2
4	8




# Binary Recursion

## Example – 4 (Continued):

- Recursive trace

	A
0	6
1	5
2	3
3	2
4	8






# Binary Recursion

## Example – 4 (Continued):

- Recursive trace

A	
0	6
1	5
2	3
3	2
4	8




# Binary Recursion

## Example – 4 (Continued):

- Recursive trace

A	
0	6
1	5
2	3
3	2
4	8




# Binary Recursion

## Example – 4 (Continued):

- Recursive trace

	A
0	6
1	5
2	3
3	2
4	8



# Binary Recursion

## Example – 5

- **The Fibonacci Number**  
1, 1, 2, 3, 5, 8, 13, 21, 34, 55, . . . . .
- Each number after the second number is the sum of the two preceding numbers.
- These numbers can naturally be defined recursively :

$$F(n) = \begin{cases} 1 & \text{if } n = 0 & \leftarrow \text{Base Case-1} \\ 1 & \text{if } n = 1 & \leftarrow \text{Base Case-2} \\ F(n-1) + F(n-2) & \text{if } n > 1 & \leftarrow \text{Recursive Case} \end{cases}$$

# Binary Recursion

## Example – 5 (Continued)


- Recursive Implementation of Fibonacci Function

```
public static int fib(int n)
{
    if (n < 2)
        return 1;                // base cases
    else
        return fib(n-1)+fib(n-2); // recursive part
}
```

# Binary Recursion

## Example – 5 (Continued)

- Recursive Trace of Fibonacci Function: fib(5)



# Linear Recursion

## Example – 6: Binary Search

- **Problem:** Given  $S = \{s_0, s_1, \dots, s_{n-1}\}$  is a sorted sequence of  $n$  integers, and an integer  $x$ . Search whether  $x$  is in  $S$ .
- **Binary Search Algorithm:**
  - If the sequence is empty, return  $-1$ .
  - Let  $s_i$  be the middle element of the sequence.
    - If  $s_i = x$ , return its index  $i$ .
    - If  $s_i < x$ , apply the algorithm on the subsequence that lies above  $s_i$ .
    - Otherwise, apply the algorithm on the subsequence of  $S$  that lies below  $s_i$ .

# Linear Recursion

## Example – 6 (continued): Binary Search

- Implementation:

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                  // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```



# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                  // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

i=2

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                    // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

search(a, 0, 5, 14)

# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

i=4

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                  // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

search(a, 0, 5, 14)

search(a, 3, 5, 14)

# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                  // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

i=2

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                  // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

search(a, 0, 5, 2)

# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

i=0

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                  // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

search(a, 0, 5, 2)

search(a, 0, 1, 2)

# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

i=2

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                  // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

search(a, 0, 5, 5)

# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

i=0

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                  // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

search(a, 0, 5, 5)

search(a, 0, 1, 5)



# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

i=0

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                  // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

search(a, 0, 5, 5)

search(a, 0, 1, 5)

search(a, 1, 1, 5)

# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                  // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

i=2

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                  // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

search(a, 0, 5, 21)

# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

i=4

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                  // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

search(a, 0, 5, 21)

search(a, 3, 5, 21)

# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

i=5

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                  // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

search(a, 0, 5, 21)

search(a, 3, 5, 21)

search(a, 5, 5, 21)

# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                    // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

search(a, 0, 5, 21)

search(a, 3, 5, 21)

search(a, 5, 5, 21)

search(a, 6, 5, 21)

# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                  // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

i=2

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                  // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

search(a, 0, 5, 12)



# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

i=4

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                    // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

search(a, 0, 5, 12)

search(a, 3, 5, 12)

# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

i=3

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                    // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

search(a, 0, 5, 12)

search(a, 3, 5, 12)

search(a, 3, 3, 12)

# Linear Recursion

## Example – 6 (continued): Binary Search

– Implementation:

a	2	5	7	11	14	20
---	---	---	---	----	----	----

```
public static int search(int a[], int lo, int hi, int x)
{
    if (lo > hi) return -1; // Basis
    else{                    // Recursive part
        int i = (lo+hi/2);
        if(a[i] == x) return i;
        else if(a[i] < x)
            return search (a, i+1, hi, x)
        else
            return search (a, lo,i-1, x);
    }
}
```

search(a, 0, 5, 12)

search(a, 3, 5, 12)

search(a, 3, 3, 12)

search(a, 4, 3, 12)