

King Saud University

College of Engineering

IE – 341: “Human Factors”

Spring – 2016 (2<sup>nd</sup> Sem. 1436-7H)

Chapter 3. Information Input and Processing

Part – 1\*

Prepared by: Ahmed M. El-Sherbeeny, PhD

# DISPLAYING INFORMATION

- Human information input and processing depends on the sensory reception of relevant **external stimuli** which contain the information
- The original source of information (the **distal stimulus**) is some object, event, or environmental condition.
- Information from the distal stimulus may come to us:
  - **directly** (e.g. direct observation of plane), or
  - **indirectly** (e.g. radar or telescope).

# Cont. DISPLAYING INFORMATION

- In the case of **indirect sensing**, the new distal stimuli may be
  - **coded stimuli** (e.g. visual or auditory displays), or:
  - **reproduced stimuli** (e.g. TV, radio, hearing aids)
  - In both cases the coded or reproduced stimuli become the actual distal stimuli to the human sensory receptors.
- Human factors are required when *indirect* sensing applies.
- **Display** is a term that applies to any indirect method of presenting information (e.g. highway traffic sign, radio).

## INFORMATION PRESENTED BY DISPLAYS (General)

- Information presented by displays can be **dynamic** or **static**.
- **Dynamic information:** changes continuously or is subject to change through time. Examples are: traffic lights, radar displays, temperature gauges.
- **Static information:** remains fixed over time. e.g: alphanumeric data, traffic signs, charts, graphs, labels.  
Note that static information presented through **VDT's** (video display terminals) is considered static information.

## INFORMATION PRESENTED BY DISPLAYS (Detailed)

- **Quantitative:** such as temperature or speed.
- **Qualitative:** represents approximate value, trend or rate of change.
- **Status:** reflects the condition of a system (such as on or off, and traffic lights).
- **Warning and signal:** indicating danger or emergency.

## INFORMATION PRESENTED BY DISPLAYS (Detailed)

- **Representational:** pictorial or graphical representation of objects, areas, or other configurations, e.g. photographs, maps, heartbeat oscilloscope.
- **Identification:** used to identify a condition, situation or object, e.g. traffic lanes, colored pipes.
- **Alphanumeric and symbolic:** e.g. signs, labels, printed material, computer printouts.
- **Time-phased:** display of pulsed or time-phased signals. The duration and inter-signal intervals are controlled.

# SELECTION OF DISPLAY MODALITY

- Visual or auditory displays? Tactual sense?  
The selection of the **sensory modality** depends on a number of considerations.
- Table 3.1 helps in making a decision regarding visual or auditory presentation of information.

**TABLE 3-1**  
WHEN TO USE THE AUDITORY OR VISUAL FORM OF PRESENTATION

<b>Use auditory presentation if:</b>	<b>Use visual presentation if:</b>
<b>1</b> The message is simple.	<b>1</b> The message is complex.
<b>2</b> The message is short.	<b>2</b> The message is long.
<b>3</b> The message will not be referred to later.	<b>3</b> The message will be referred to later.
<b>4</b> The message deals with events in time.	<b>4</b> The message deals with location in space.
<b>5</b> The message calls for immediate action.	<b>5</b> The message does not call for immediate action.
<b>6</b> The visual system of the person is overburdened.	<b>6</b> The auditory system of the person is overburdened.
<b>7</b> The receiving location is too bright or dark-adaptation integrity is necessary.	<b>7</b> The receiving location is too noisy.
<b>8</b> The person's job requires moving about continually.	<b>8</b> The person's job allows him or her to remain in one position.

Source: Deatherage, 1972, p. 124, Table 4-1.

# CODING OF INFORMATION

- **Coding** takes place when the original stimulus information is converted to a new form and displayed symbolically.
- Examples are:
  - radar screens where the aircrafts are converted and presented as dots on the screen
  - maps displaying populations of different cities with different symbols.



# CODING OF INFORMATION (Cont.)

- Information is coded along various dimensions.
- Examples:
  - Varying the size, brightness, color and shape of targets on a computer screen.
  - Varying the frequency, intensity, or on-off pattern of an audio warning signal.
- Each of the above variations constitutes a dimension of the displayed stimulus, or a **stimulus dimension**.

# CODING OF INFORMATION (Cont.)

- The usefulness of any stimulus dimension in conveying information depends on the ability of people to:
  - Identify a stimulus based on its position along the stimulus dimension (such as identifying a target as bright or dim, large or small)
    - This is an example of **absolute judgment**.
  - Distinguish between two or more stimuli which differ along the stimulus dimension (such as indicating which of the two stimuli is brighter or larger)
    - This is an example of **relative judgment**.

# CHARACTERISTICS OF A GOOD CODING SYSTEM

- **Detectability** of codes:
  - stimulus must be detectable by human sensory mechanisms under expected environmental conditions
  - e.g. is worker able to see the control knob in mine?
- **Discriminability** of codes:
  - every code symbol must be discriminable (differentiable) from other symbols
  - the number of coding levels is important
- **Meaningfulness** of codes:
  - coding system should use codes meaningful to user
  - Meaning could be
    - **inherent** in the code (e.g. bent arrow on traffic sign)
    - or **learned** (e.g. red color for danger)
  - Meaningfulness: related to **conceptual compatibility**

## CHARACTERISTICS OF A GOOD CODING SYSTEM (cont.)

- **Standardisation** of codes:
  - when a coding system is to be used by different people in different situations, it is important that the codes be standardised, and kept the same for different situations
  - e.g. meaning of the red color in different parts of a factory
- Use of **multidimensional codes**:
  - this can increase the number and discriminability of coding stimuli used.

# COMPATIBILITY

- It is the relationship between the stimuli and the responses to human expectations.
- A major goal in any design is to make it compatible with human expectations.
- It is related to the process of **information transformation**
  - the *greater* the degree of compatibility, the *less* recording must be done to process information
  - This leads to faster learning and response time, less errors, and reduced mental workload.
  - People like things that work as they expect them to work.

# COMPATIBILITY (Cont.)

- Four types of compatibility:
  - Conceptual
  - Movement
  - Spatial
  - Modality
- **1. Conceptual compatibility:**
  - related to degree that codes, symbols correspond to conceptual associations people have.
  - It relates to how meaningful codes and symbols are to people who use them.
  - e.g.: airplane symbol to denote an airport on a map means much more than a square or circle
  - e.g.: creating meaningful abbreviations and names for computer applications

# COMPATIBILITY (Cont.)

- **2. Movement compatibility:**
  - relates to the relationship between the movement of the displays and controls and the response of the system being displayed or controlled.
  - e.g.: to increase the volume on the radio, we expect to turn the knob clockwise.
  - e.g.: upward movement of a pointer is expected to correspond to an increase in a parameter
- **3. Spatial Compatibility**
  - Refers to the physical arrangement in space of controls and their associated displays
  - e.g. how displays are lined-up with respect to corresponding control knobs

# COMPATIBILITY (Cont.)

- 4. **Modality compatibility:**
  - refers to the fact that certain stimuli-response modality combinations are more compatible with some tasks than with others.
  - e.g.: responding to a verbal command that needs verbal action is faster than responding to a written or displayed command requiring the same verbal action.